

ARCTIC RIG

Well-Type	1. Conventional 2. Shale 3. Horizontal
Size	250, 350, or 500 Tons
Horsepower	700, 1000, 1250, 1500, or 2000
Rig Power	AC , DC, or Mechanical
Engine Type	CAT 3512C
Mast	Doubles or Triples
Mast Type	Telescopic or Cantilever
Mast Raising System	Cylinder Raised or Sling-Line Raised
Mast Height	120+ ft
Substructure Type	Slingshot-cylinder, Slingshot-winch Box on Box, or Cantilever
Setback Capacity	250,000 lbs, 320,000lbs 500,000 lbs, or 600,000 lbs
Drilling Moving System	None, Trailerized, or Powered Wheel
Drill Floor Height	20 ft, 25 ft, 34 ft, or 35 ft
NOV Drawworks Type	Contact Regional Sales
Horsepower	
Hoisting Capacity	
NOV Top Drive	Contact Regional Sales
Capacity	
Continuous Drilling Torque	
NOV Iron Roughneck	Contact Regional Sales
Makeup Torque	
Breakout Torque	
BOP Type	Contact Regional Sales
Bore Size	
Working Pressure	



Driller's Controls	AMPHION
Driller's Cabin	HVAC
Rotary Table	Contact Regional Sales
Opening	
NOV Mud Pumps	Contact Regional Sales
Horsepower	
Optional Equipment	Contact Regional Sales
	1
	2