

## XT-M™ CONNECTION MECHANICAL CHARACTERISTICS

	OD	Nominal Weight	Grade	Premium Tube Tensile Strength	Connection	Tool Joint OD	Tool Joint ID	SmoothEdge® OD	Adjusted Weight	Minimum MUT	Recommended MUT
	in	lb/ft		lbs		in	in	in	lb/ft	ft-lb	ft-lb
Standard	3.500	13.30	S-135	381,900	XT-M38	4.750	2.563		14.62	13,900	16,700
Standard	3.500	15.50	S-135	451,100	XT-M38	4.750	2.438		16.99	15,400	18,400
Standard	4.000	14.00	S-135	403,500	XT-M39	4.875	2.688	5.250	15.47	15,800	18,900
Standard	4.000	15.70	S-135	456,900	XT-M39	5.000	2.563	5.313	17.47	18,600	22,300
Standard	4.500	16.60	S-135	468,300	XT-M46	6.250	3.250		19.26	32,100	38,500
Standard	4.500	20.00	S-135	581,200	XT-M46	6.250	3.250		22.81	32,100	38,500
Standard	5.000	19.50	S-135	560,800	XT-M50	6.625	3.750		22.37	35,000	42,000
Standard	5.000	25.60	S-135	746,400	XT-M50	6.625	3.500		28.58	41,800	50,200
Standard	5.500	21.90	S-135	620,600	XT-M54	6.625	4.000		24.19	37,800	45,400
Standard	5.500	24.70	S-135	704,300	XT-M54	6.625	4.000	6.813	26.81	37,800	45,400
Standard	5.875	23.40	S-135	666,500	XT-M57	7.000	4.250		26.15	42,900	51,500
Standard	5.875	26.30	S-135	757,100	XT-M57	7.000	4.250		28.99	42,900	51,500
Standard	6.625	25.20	S-135	697,400	XT-M69	8.500	5.250		29.15	77,200	92,700
Standard	6.625	27.70	S-135	760,400	XT-M69	8.500	5.250		31.10	77,200	92,700